sawtechno.ru
mail@sawtechno.ru
121351, Москва г., а/я 35
(499) 322-06-38

Общество с ограниченной ответственностью
«Научно-производственное предприятие «Техно-ПАРК»
(ООО «НПП «Техно-ПАРК»)
Юридический и фактический адрес: 121351, г. Москва,
ул. Ивана Франко, д. 48

Технические характеристики генератора

SG-3030LC

Производитель: Epson

Поставщик: ООО «НПП «Техно-ПАРК»

Научно-производственное предприятие ООО «НПП «Техно-ПАРК» разрабатывает и поставляет полосно-пропускающие радиочастотные фильтры на поверхностных акустических волнах (ПАВ) и устройства на их основе.

CRYSTAL OSCILLATOR (SPXO)

32.768 kHz

SG-3030CM / LC / JF / JC
SG-3040LC / JC

- Built-in 32.768 kHz crystal unit allows adjustment-free efficient operation.
- Use of C-MOS IC enables reduction of current consumption.
- VIO controls swing amplitude.

Pb Free
RoHS Compliant

CM Type **CM,LC, JF,JC Type**

Product Number (please contact us)
SG-3030CM : X1B000211xxxx00
SG-3030LC : Q3102LC02000100
SG-3030JF : Q3102JF02000100
SG-3030JC : Q3102JC02000100
SG-3040LC : Q3103LC02000100
SG-3040JC : Q3103JC01000100

SG-3030CM

SG-3030LC
SG-3040LC

Actual size

SG-3030JF

SG-3030JC
SG-3040JC

CM Type.	LC Type.	JF Type.	JC Type.

Specifications (characteristics)

Item	Symbol	Specifications		Conditions / Remarks
		SG-3030CM / LC / JF / JC	SG-3040LC / JC	
Output frequency range	f_0	32.768 kHz		
Supply voltage	V_{CC}	1.5 V to 5.5 V	0.9 V to 3.6 V	
Interface power supply voltage	V_{IO}	1.5 V to 5.5 V	0.9 V to 3.6 V	
Storage temperature	T_stg	-55 °C to +125 °C		Storage as single product
Operating temperature	T_use	-40 °C to +85 °C		
Frequency tolerance	f_tol	$5 \pm 23 \times 10^{-6}$		+25 °C, V_{CC}=3.3 V (SG-3040: V_{CC}=1.2 V)
Frequency temperature coefficient	f_0-Tc	$+10 \times 10^{-6}$ / -120×10^{-6}		-20 °C to +70 °C (+25 °C is reference)
Frequency / voltage coefficient	f_0-V_{CC}	$\pm 2 \times 10^{-6}$ / V Max.	$\pm 5 \times 10^{-6}$ / V Max.	+25 °C
Current consumption	I_{CC}	2 µA Max.	3.1 µA Max.	3.3 V, No load condition
Symmetry	SYM	45 % to 55 %		1/2 V_{CC}(V_{IO})level (SG-3040: V_{IO}=1.2 V to 3.6 V)
Output voltage	V_{OH}	V_{IO}-0.4 V Min.		I_{OH}=-0.4 mA (SG-3040: V_{IO}=1.2 V to 3.6 V)
	V_{OL}	0.4 V Max.		I_{OL}= 0.4 mA (SG-3040: V_{IO}=1.2 V to 3.6 V)
Output load condition (CMOS)	L_CMOS	15 pF Max.		CMOS load
Rise time / Fall time	t_r / t_f	200 ns Max.	100 ns Max.	CMOS load:20 % V_{CC}(V_{IO}) to 80 % V_{CC}(V_{IO})level (SG-3040: V_{IO}=1.2 V to 3.6 V)
Start-up time	t_str	1 s Max.	3 s Max.	Time at minimum Supply voltage to be 0 s +25 °C (SG-3030: V_{CC}= 2.0 V to 5.5 V)
Frequency aging	f_aging	$\pm 5 \times 10^{-6}$ / year Max.		+25 °C, V_{CC}= 3.3 V, First year

Unless otherwise stated, characteristics (specifications) shown in the above table are based on the rated operating temperature and voltage condition.

Block diagram



If V_{IO} function is not used, connect #1 to V_{CC}.

Product name
(Standard form)

SG-3030 LC 32.768000kHz B
① ② ③ ④

①Model ②Package type ③Frequency

④Frequency tolerance (B: $5 \pm 23 \times 10^{-6}$,+25 ºC)

External dimension and Footprint (Recommended)

(Unit:mm)



PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.

WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

►Explanation of the mark that are using it for the catalog

Pb Free	►Pb free.
RoHS Compliant	►Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
For Automotive	►Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
Automotive Safety	►Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc).

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
  / Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.